

VOLVO DOUBLE DRUM COMPACTORS

# DD31HF, DD38HF



MORE CARE. BUILT IN.



# ULTRA PERFORMANCE IN A SMALLER PACKAGE

Volvo DD31HF and DD38HF vibratory compactors offer high performance for both commercial and main-line paving contractors in all three critical areas of compaction: productivity, density, and smoothness. Both models also have full-day fuel operation, large water capacity, and high frequency, making efficiency a strength of this line.

## Performance Features

### • Comfort and safety

- Isolated vibratory drums and 4-point isolation of the operator platform to minimize vibration feedback
- Dual-side access, spring-applied, hydraulically released parking brake with test switch, Roll Over Protective Structure (ROPS), emergency stop switch, seat switch, and propulsion control with neutral start
- Seat belt warning system: continuous alarm until seat belt is fastened
- Fully adjustable sliding seat

### • Drum performance

- Durable carbon steel and thick shells prolong drum life

### • Gradeability and tractability

- The TwinLock™ traction control and torque transfer system minimizes drum slippage, delivering superior drum control at all speeds and in both directions

### • Industry-leading water system

- 299 l water tank, standard pressurized water system, hand-serviceable water nozzles, and double-filtration
- Water flows only when the compactor is moving (in automatic mode)

### • Serviceability

- Unobstructed daily checkpoints, easy-to-lift engine enclosure, plus ground-level access to the engine, radiator, battery, and filters
- Color-coded service charts show detailed checkpoints, service intervals, and proper lubricants

## Options

- Cocoa mats
- Edge compactor
- Flashing strobe
- Foldable ROPS
- Gauge package (includes engine coolant temperature, engine oil pressure and voltmeter)
- Hazard and turn signals
- Inside wipers
- LED high intensity work lights
- Low fuel alarm
- Remote hydraulic test ports
- Special paint
- Steering knob
- Urethane wipers
- Vandal cover
- Water strainer



# SPECIFICATIONS

Model		DD31HF	DD38HF
<b>Machine Weight (w/ ROPS / FOPS)</b>			
Operating Weight	kg	3 102	3 809
Static Weight @ Front Drum	kg	1 419	1 780
Static Weight @ Rear Drum	kg	1 682	2 029
Shipping Weight	kg	2 871	8 577
<b>Dimensions</b>			
Length	mm	2 556	2 556
Width	mm	1 363	1 485
Height (top of steering wheel)	mm	1 826	1 826
Height (top of ROPS)	mm	2 527	2 529
Drum Base	mm	1 725	1 725
<b>Drums</b>			
Width	mm	1 250	1 375
Diameter	mm	736	739
Shell Thickness (nominal)	mm	14	16
Finish		Machined / chamfered edge	
<b>Vibration</b>			
Frequency	Hz	70	70
Centrifugal Force	kN	36	36
Nominal Amplitude	mm	0,38	0,33
Lubrication		Oil splash	
Type System		Open-loop, series circuit	
Vibrating Drums		Both or front only	
Vibration Isolation		6 shear block isolators per drum	
<b>Propulsion</b>			
Type		Closed-loop, hydrostatic, TwinLock	
Drum Drive		Pump: axial-piston; Motor: radial piston, low-speed, high-torque	
Speed Range	km/h	0 - 10	0 - 10
Gradeability (theoretical)		49%	38%
<b>Engine</b>			
Make / Model		Kubota V2203M Tier 4A	
Engine Type		4-cylinder diesel	
Rated Power @ Installed Speed	kW	31,3	31,3
Electrical		12 volts DC, negative ground; 40 A alternator	
Battery		800 CCA	800 CCA
<b>Brakes</b>			
Service		Dynamic hydrostatic through propulsion system	
Parking / Secondary		Spring-applied, hydraulically released on each drum drive	
<b>Steering</b>			
Design		Centerpoint articulation	
Type System		Double-acting, hydraulic, single-cylinder	
Articulation Angle		+ / - 30°	+ / - 30°
Outside Turning Radius	mm	3 847	3 907
<b>Water System</b>			
Type		Pressurized	
Pump		Electric, diaphragm	
Nozzle Quantity Per Drum		5 hand-serviceable nozzles	
Tank Capacity	l	299	299
Filters		100 mesh screen @ nozzles, 80 mesh in-line	
Drum Wipers Type		Spring-loaded, self-adjusting, neoprene wipers	
<b>Miscellaneous</b>			
Fuel Capacity	l	68	68
Hydraulic Capacity	l	84,8	84,8
Oscillation		+ / - 10°	+ / - 10°
Curb Clearance	mm Vibration	483	608
	mm Traction	615	615
Side Clearance	mm	57	57

Product improvement is a continuing goal at Volvo. Designs and specifications are subject to change without notice or obligation.



Volvo Construction Equipment is different. Our machines are designed, built and supported in a different way. That difference comes from an engineering heritage of over 175 years. A heritage of thinking first about the people who actually use the machines. About how to help them be safer, more comfortable, more productive. About the environment we all share. The result of that thinking is a growing range of machines and a global support network dedicated to helping you do more. People around the world are proud to use Volvo. And we're proud of what makes Volvo different – **More care. Built in.**



*Not all products are available in all markets. Under our policy of continuous improvement, we reserve the right to change specifications and design without prior notice. The illustrations do not necessarily show the standard version of the machine.*

# **VOLVO**

**Volvo Construction Equipment**  
**[www.volvoce.com](http://www.volvoce.com)**

Ref. No. VOE 21 C 100 4027  
Printed in Sweden 2009.08-5,0  
Volvo, Sweden

English